



327

 depl. 01021

Loptasti ventil sa ugrađenom nepovratnom klapnom.



Za sisteme grejanja.
Hromiran.
Mali pad protoka.
P_{max}: 16 bar.
T_{max}: 110°C.
Patentiran.

Art				
327400	1/2"	leptir ručica	10	10
327500	3/4"	leptir ručica	10	10
327600	1"	ravna ručica	14	14
327700	1 1/4"	ravna ručica	14	14
327800	1 1/2"	ravna ručica	12	12
327900	2"	ravna ručica	11	-



510

 depl. 01045

Ventil za sprečavanje prirodne cirkulacije.



Prav ili ugaoni priključak dobija se premeštanjem čepa.
P_{max} radni: 10 bar.
T_{max} radna: 120°C.

Art				
510500	3/4"		1	20
510600	1"		1	20
510700	1 1/4"		1	20



519

 depl. 01007

Regulacioni diferencijalni by-pass ventil.



Sa stepenom skalom.
P_{max} radni: 10 bar.
T_{max} radna: 110°C.

Art		Područje regulacije m. v. s.		
519500	3/4"	1+6	1	50
519504	3/4"	10+40	1	50
519700	1 1/4"	1+6	1	10

336

Nosač predmontiranih sigurnosnih elemenata.



Za grejne uređaje.
Sastoji se od: odzračnog ventila, sigurnosnog ventila, manometra i automatskog nepovratnog ventila za ekspanzione posude.

Art				
336630	3/4"	3 bar	1	5

302

Kotlovska sigurnosna grupa sa izolacijom.



Za sisteme grejanja.
Sastoji se od: odzračnog ventila, sigurnosnog ventila i manometra.

Art				
302631	1"	3 bar	1	10



683

 depl. 01040

Priključak za merač protoka.



Navojni priključci Ž i priključci za merenje pritiska.
P_{max} radni: 10 bar.
T_{max} radna: 110°C.

Art				
683005	3/4"		1	-
683006	1"		1	-



683

 depl. 01040

Priključak za merač protoka.



Telo od čelika. Prirubnički priključci. U paru sa kontra prirubnicama: EN 1092-1 (ex UNI 2276). DN 32+DN 100, PN 6; (ex UNI 2278) DN 125+DN 200, PN 16.
T_{max} radna: 110°C.
Sadrži i priključke za merenje pritiska, kontra prirubnice, zavrtnje i navrtke.

Art				
683030	DN 132		1	-
683040	DN 140		1	-
683050	DN 150		1	-
683060	DN 165		1	-
683080	DN 180		1	-
683100	DN 100		1	-
683120	DN 125		1	-
683150	DN 150		1	-
683170	DN 175		1	-
683200	DN 200		1	-

Za merenje protoka upotrebljavamo merač protoka FLOMET art. 130000 (str. 174).

100

Par igličastih priključaka za merenje protoka.



Navojni priključak: 1/4" Ž.
P_{max} radni: 10 bar.
T_{max} radna: 110°C.

Art				
100010			1	-