

**TERMOSTATSKI VENTILI**



220

 depl. 01034



**Ugaoni radijatorski ventil za termostatsko ili elektrotermičko upravljanje.**

Hromiran.  
Za gvozdene cevi.  
(Za bakarne cevi sa adapterom serije 441).  
P<sub>max</sub>: 10 bar.  
T<sub>min</sub> - T<sub>max</sub>: 5÷100°C.

Art.	Ø	K <sub>vs</sub> (m <sup>3</sup> /h)*		
220302	3/8"	2,29	1	20
220402	1/2"	2,39	1	20
220500	3/4" bez gumene zaptivke	3,19	1	20



224

 depl. 01034



**Ugaoni radijatorski ventil za termostatsko ili elektrotermičko upravljanje.**

Hromiran.  
Za gvozdene cevi.  
(Za bakarne cevi sa adapterom serije 441).  
P<sub>max</sub>: 10 bar.  
T<sub>min</sub> - T<sub>max</sub>: 5÷100°C.

Art.	Ø	K <sub>vs</sub> (m <sup>3</sup> /h)*		
224302	3/8"	0,93	1	20
224402	1/2"	1,39	1	20

221

 depl. 01034



**Prav radijatorski ventil za termostatsko ili elektrotermičko upravljanje.**

Hromiran.  
Za gvozdene cevi.  
(Za bakarne cevi sa adapterom serije 441).  
P<sub>max</sub>: 10 bar.  
T<sub>min</sub> - T<sub>max</sub>: 5÷100°C.

Art.	Ø	K <sub>vs</sub> (m <sup>3</sup> /h)*		
221302	3/8"	1,05	1	20
221402	1/2"	1,52	1	20
221500	3/4" bez gumene zaptivke	2,20	1	20



227

 depl. 01034



**Ugaoni radijatorski ventil za termostatsko ili elektrotermičko upravljanje.**

Hromiran.  
Za bakarne cevi.  
P<sub>max</sub>: 10 bar.  
T<sub>min</sub> - T<sub>max</sub>: 5÷100°C.

Art.	Ø	K <sub>vs</sub> (m <sup>3</sup> /h)*		
227402	1/2" 23 p.1,5	1,39	1	20



222

 depl. 01034



**Ugaoni radijatorski ventil za termostatsko ili elektrotermičko upravljanje.**

Hromiran.  
Za bakarne cevi.  
P<sub>max</sub>: 10 bar.  
T<sub>min</sub> - T<sub>max</sub>: 5÷100°C.



Art.	Ø	K <sub>vs</sub> (m <sup>3</sup> /h)*		
222402	1/2" 23 p.1,5	2,39	1	20



441

**Konusni adapter.**

Za ventile serije 220, 221, 224 i 225.  
Hromiran.  
Za bakarne cevi.

Art.			
441312	3/8" - Ø 12 dvokonusni	100	-
441414	1/2" - Ø 14 jednokonusni	100	-
441415	1/2" - Ø 15 jednokonusni	100	-
441416	1/2" - Ø 16 dvokonusni	100	-



223

 depl. 01034



**Prav termostatski radijatorski ventil.**

Hromiran.  
Za bakarne cevi.  
P<sub>max</sub>: 10 bar.  
T<sub>min</sub> - T<sub>max</sub>: 5÷100°C.

Art.	Ø	K <sub>vs</sub> (m <sup>3</sup> /h)*		
223402	1/2" 23 p.1,5	1,52	1	20