

Cev

RAUTHERM S Cev

Za instalacije grejanja.

Materijal: peroksidno umrežen polietilen (PE-Xa), prema DIN 16892.



Zaporni sloj protiv difuzije kiseonika prema DIN 4726.

Dozvole: DIN CERTCO Reg. br. 3V226 PE-Xa ili 3V227 PE-Xa.

Boja: crvena

Oblik isporuke: koturovi, zapakovani u kartonu

*koturovi vezani PP kordelom



Mat.-Nr.	Mere mm		Vol. l/m	Masa kg/m	Pakovanje	Količina na paleti	Jedinica isporuke
	d	s					
Kotur:							
11361401120	17	2,0	0,133	0,103	120 m kotur	1800 m	120 m
11361401240	17	2,0	0,133	0,103	240 m kotur	1920 m	240 m
11361401500	17	2,0	0,133	0,103	500 m kotur	2500 m	500 m*
11361601120	20	2,0	0,201	0,123	120 m kotur	1800 m	120 m
11361601240	20	2,0	0,201	0,123	240 m kotur	1680 m	240 m
11361601500	20	2,0	0,201	0,123	500 m kotur	1500 m	500 m*
11367701120	25	2,3	0,327	0,175	120 m kotur	960 m	120 m
11367701300	25	2,3	0,327	0,175	300 m kotur	900 m	300 m*
11369001100	32	2,9	0,539	0,280	100 m kotur	800 m	100 m
Šipka:							
11361401005	17	2,0	0,133	0,103	5 m šipka	3600 m	50 m
11361601005	20	2,0	0,201	0,123	5 m šipka	2700 m	50 m
11367701005	25	2,3	0,327	0,175	5 m šipka	1800 m	25 m
11369001005	32	2,9	0,539	0,280	5 m šipka	1125 m	25 m