



## T-komad

Primenljiv u instalacijama grejanja sa  
RAUTHERM S i RAUTHERM SPEED cevima.

Materijal: mesing, pocinkovan

Osobine: sastavni deo REHAU trajno dihtujućeg spoja sa pokretnom  
navlakom (bez O prstena), prema DIN 18380 primenljiv u estrihu ili  
betonu, kao i ispod maltera, bez revizionih otvora.



Mat.-Nr.	Dimenzija	Mere mm						Masa kg/kom.	Jedinica isporuke
		a	b	c	z <sub>1</sub>	z <sub>2</sub>	z <sub>3</sub>		
<b>jednakostrani:</b>									
12502871002	16/17 - 16/17 - 16/17	39	43	39	24	28	24	0,110	5 kom.
12588771002	20 - 20 - 20	40	45	40	25	30	25	0,130	5 kom.
12535291002	25 - 25 - 25	50	59	50	28	37	28	0,220	5 kom.
12610531001	32 - 32 - 32	59	64	59	32	37	32	0,360	3 kom.
<b>izlaz redukovan:</b>									
12005431001	16/17 - 10 - 16/17	35	35	35	20	25	20	0,084	5 kom.
12005441001	20 - 10 - 20	35	36	35	20	26	20	0,097	5 kom.
12005631001	25 - 10 - 25	48	41	48	26	31	26	0,135	5 kom.
12005641001	32 - 10 - 32	54	44	54	27	34	27	0,238	5 kom.
12491071001	16/17 - 14 - 16/17	40	36	40	25	26	25	0,100	5 kom.
12588671002	20 - 16/17 - 20	39	45	39	24	30	24	0,130	5 kom.
12535691002	25 - 16/17 - 25	46	51	46	25	36	25	0,180	5 kom.
12535391002	25 - 20 - 25	48	51	48	26	36	26	0,190	5 kom.
12611631001	32 - 20 - 32	54	51	54	27	36	27	0,280	3 kom.
<b>prolaz redukovan:</b>									
12685501001	25 - 25 - 20	50	59	43	29	37	28	0,190	5 kom.
<b>izlaz i prolaz redukovani:</b>									
12588571002	20 - 16/17 - 16/17	39	45	39	24	30	24	0,110	5 kom.
12535591002	25 - 20 - 20	48	51	40	26	36	25	0,160	5 kom.
<b>izlaz proširen:</b>									
12685201001	20 - 25 - 20	42	53	42	27	31	27	0,180	5 kom.